

	Focus 320 SBR	Delta Fusion	Opel 2 & 3 Plus	Opel Keystone	Pearl	Focus 250	Focus 320	Focus ST	Opel 2 & 3 (non-cat)
Outside Dimensions (W x H x D)	45" x 44 1/4" x 24"	47 1/8" x 44 3/8" x 25 1/4"	37" x 52 1/4" x 24"	37" x 52 1/4" x 24"	36 5/8" x 38 5/8" x 24 1/8"	37" x 41" x 24"	45" x 44 1/4" x 24"	37 1/4" x 45 1/4" x 21 3/4"	37" x 49 1/2" x 24"
Crated Weight	562 lb	647 lb	553 lb	605 lb	430 lb	354 lb	562 lb	600 lb	525 lb
Firewood Length	22"	24"	18"	18"	16"	18"	22"	20"	18"
Firebox Size ¹	2.6 cubic feet	4.4 cubic feet	3.6 cubic feet	3.6 cubic feet	2.1 cubic feet	2.1 cubic feet	2.6 cubic feet	4.1 cubic feet	3.6 cubic feet
BTU Output Range ²	10,000 to 50,000	40,000 to 95,000	10,000 to 70,000	10,000 to 70,000	11,000 to 50,000	11,000 to 50,000	10,000 to 50,000	50,000	10,000 to 70,000
Heating Capacity ³	1,000 to 2,000 ft ²	3,000 ft ²	1,500 to 3,000 ft ²	1,500 to 3,000 ft ²	800 to 1,500 ft ²	800 to 1,500 ft ²	1,000 to 2,000 ft ²	1,000 ft ²	1,500 to 3,000 ft ²
EPA Certification	1.4 g/hr	1.3 g/hr	0.7 g/hr	0.7 g/hr	4 g/hr	4 g/hr	4.5 g/hr	EPA not applicable ¹⁰	note ⁴
Optimal Efficiency ⁵	75% (LHV)	69% (LHV)	80% (LHV)	80% (LHV)	76% (LHV)	76% (LHV)	77% (LHV)	N/A	N/A
Chimney	7" Excel	8" Excel	7" Excel	7" Excel	7" Excel	7" Excel	7" Excel	8" Excel	7" Excel
Door Finish	Metallic Black	Metallic Black	Metallic Black	Metallic Black	Metallic Black	Metallic Black	Metallic Black	Metallic Black	Metallic Black
Decorative Trims	N/A	N/A	Opel2: N/A Opel3: PDTB, PDTG, PDTTP	N/A	N/A	N/A	N/A	N/A	Opel2: N/A Opel3: PDTB, PDTG, PDTTP
Ash Pan	N/A	N/A	FO-AP ⁸	FO-AP ⁸	N/A	N/A	N/A	N/A	FO-AP ⁸
Gravity Vent Kit	FO-V2	FO-V2	FO-V2	FO-V2	FO-V2	FO-V2	FO-V2	FO-V2	FO-V2
Rectangular Gravity Vent Kit	FO-V3	FO-V3	FO-V3	FO-V3	FO-V3	FO-V3	FO-V3	FO-V3	FO-V3
Gravity Vent Damper	N/A	N/A	FO-D ⁹	N/A	N/A	N/A	N/A	N/A	FO-D ⁹
Contemporary Grill	FO-VGC	FO-VGC	FO-VGC	FO-VGC	FO-VGC	FO-VGC	FO-VGC	FO-VGC	FO-VGC
Heat Dump	FO-HD	N/A	FO-HD	FO-HD	FO-HD ⁹	FO-HD	FO-HD	N/A	FO-HD
Internal Blower	FO-FDHB5-N ⁸	FO-FDHB5-N ⁸	FO-FDHB5-N ⁸	FO-FDHB5-N ⁸	FO-FDHB8 ⁹	N/A – See Inline Fan	FO-FDHB5-N ⁸	N/A	FO-FDHB5-N ⁸
Central Heating Blower 635cfm	FO-FDHB6-1	FO-FDHB6-1	FO-FDHB6-1	FO-FDHB6-1	N/A	N/A	FO-FDHB6-1	N/A	FO-FDHB6-1
Central Heating Control	FO-FDHC6	FO-FDHC6	FO-FDHC6	FO-FDHC6	N/A	N/A	FO-FDHC6	N/A	FO-FDHC6
Central Heating Tee	FO-T	FO-T	FO-T	FO-T	N/A	N/A	FO-T	N/A	FO-T
Zone Heating Option	FO-FDHCZ1 & FO-FDHCZ2	FO-FDHCZ1 & FO-FDHCZ2	FO-FDHCZ1 & FO-FDHCZ2	FO-FDHCZ1	N/A	N/A	FO-FDHCZ1 & FO-FDHCZ2	N/A	FO-FDHCZ1 & FO-FDHCZ2
Electric Thermostat	N/A	N/A	FO-FDHC4	FO-FDHC4	N/A	N/A	FO-FDHC4	N/A	FO-FDHC4
Rock Retainer Kit	FO-KN	FO-KDF	FO-KP3	FO-KK	N/A	N/A	FO-KN	FO-KR	FO-KP3
Clean Facing	FO-F2 + FO-V2/V3 (2X)	N/A	FO-F3 + FO-V2/V3 (2X)	N/A	N/A	N/A	FO-F2 + FO-V2/V3 (2X)	N/A	FO-F2 + FO-V2/V3 (2X)
Inline Fan	FO-CIF	N/A	N/A	N/A	N/A	FO-CIF & FO-CID	FO-CIF	N/A	FO-CIF
Gas Log Provision ⁶	N/A	N/A	YES	YES	N/A	N/A	N/A	YES	YES
Masonry Chimney Option	FO-FDM7	FO-FDM8	FO-FDM7	FO-FDM7	FO-FDM7	FO-FDM7	FO-FDM7	FO-FDM8	FO-FDM7
Firescreen	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	FO-FDFS
Outside Air ⁷	4", meets R2000	4", meets R2000	4", meets R2000	4", meets R2000	4", meets R2000	4", meets R2000	4", meets R2000	4", meets R2000	4", meets R2000
Mobile Home Approved	YES	NO	NO	NO	NO	NO	YES	NO	NO
Louver or Grill Options	Black Louvers included	Black Decorative Faceplate included	Black, Pewter or Gold Plated Louvers or Decorative Grills ⁸	Top Keystone Louver - FO-OPLK	Black Decorative Faceplate included	Black Louvers included	Black Louvers included	Black Louvers included	Black, Pewter or Gold Plated Louvers or Decorative Grills ⁸

note 1: Based on overall firebox dimensions, EPA official firebox dimensions are smaller.
note 2: Actual BTU output depends on many factors, but primarily on the quality of the wood burned.
note 3: Depends primarily on wood quality, ambient air temperature and building heat loss.
note 4: The non-catalytic Opel is available in Canada only and is certified as an exempt appliance to CSA B415.1 with a rate of 2.8 grams/hour. With the optional catalytic combustor (FO-FDCCO), the Opel is EPA certified to comply with 2015 particulate emissions standards until 2020 @ 3.7 grams/hour.
note 5: Low Heating Value (LHV), using data generated under the best circumstances and CSA B415.1-10 calculations

note 6: These fireplaces may be drilled out to accept an after market gas log assembly. You may not install a gas lighter in any RSF fireplace because the high firebox temperatures will burn out the log lighter very quickly.
note 7: All RSF models come equipped to accept a 4" outside air duct, a 5" can also be used. All models can also be installed to operate using room air.
note 8: N/A on fireplaces installed with the Clean Face Option.
note 9: Negates EPA certification.
note 10: The Focus ST can be sold in Canada and the USA as per Subpart AAA of the 2015 EPA Standards of Performance for New Residential Wood Heaters Vol. 80, No. 50.

Note: All information and dimensions provided in this brochure are for general information purposes only. You must follow the installation instructions which accompany each fireplace to ensure your particular installation is done safely and correctly. These dimensions are modified from time to time so please confirm them with the current installation instructions before construction.