

## EO-08LLG-IN

### Long Linear Intake Grill

This optional grill is for the air intake of the Renaissance Uptown 600 Fireplace. It replaces the two inlet grills provided with the fireplace. If desired, a Long Linear Outlet Grill (EO-08LLG-OUT) can also be ordered to be installed above the fireplace as the hot air outlet.

#### Long Linear Intake Grill Specifications

Width	37"	(0.940 m)
Height	6"	(152 mm)
Depth	3.188"	(81 mm)
Minimum height of 08LLG-IN above the floor.	1.5"	(38 mm)
Minimum height that the fireplace must be raised in order to install the 08LLG-IN.	12"	(305 mm)
Minimum ceiling height measured from the base of the fireplace to the ceiling.	7'	(2.4m)

The Long Linear Intake Grill does not connect directly to the fireplace. It permits air to enter the fireplace enclosure, which the fireplace requires to maintain a safe installation. It is to be installed below the fireplace opening. The air entering the enclosure will circulate through the fireplace and exit through the hot air outlets at the top.

1. Below the fireplace opening, frame the opening for the Long Linear Intake Grill with 2x4's or metal studs. The framed opening should be 35 1/2" wide and 4 3/4" tall, centered on the fireplace. Refer to the Table above for minimum and maximum clearance requirements from the floor.
2. Cover the wall as specified in the fireplace installation manual with cement boards, leaving the framed opening free for the installation of the grill.
3. Insert the Long Linear Intake Grill into the opening and fasten it to the framing with the four screws provided.

**WARNING: ONLY USE GRILLS CERTIFIED BY RENAISSANCE FIREPLACES. SUBSTITUTING THE GRILLS PROVIDED WITH THE FIREPLACE OR FIREPLACE OPTIONS WILL RESULT IN LOSS OF WARRANTY AND POSE A FIRE HAZARD.**

**DO NOT BLOCK AIR FLOW IN FRONT OF THE INTAKE GRILLS. YOU MUST ALLOW FREE AIR MOVEMENT.**